

APC Online 5k / 6kVA

Introducing state of the art, Next Gen Online UPS

SRC5KUXI, SRC6KUXI



- 1 >94% efficiency (Double-conversion)
Save Rs 10k every year*
- 2 Save even more in **Green mode**, 98% efficiency
- 3 **0.9 power factor** (4.5kW output for 5kVA, 5.4kW for 6kVA)
- 4 **Separate Bypass** input
- 5 **High-Power Charger**: 1500W max
- 6 **SMF / Flooded** battery selectable
- 7 **Genset-compatible**
- 8 **Graphical LCD** easy-to-use interface
- 9 **SmartSlot** for all management card options
- 10 EPO, USB, RS232C, Dry Contacts
- 11 **Rack/Tower** convertible, 3U in rack
- 12 **Paralleling option** available

Product feature	SRC5KUXI	SRCE6KUXI
Input Specifications		
Nominal Input Voltage	230 V	
Input Frequency	40-70 Hz	
Input Voltage	100-285 V (Output derated linearly to 50% of UPS capacity @ < 160V)	
Input Power Factor	0.98	
Output Specifications		
Output Power Capacity	4500 W / 5000 VA	5400 W / 6000 VA
Nominal Output Voltage	230 V	
Other Programmable Voltages	220 V / 240 V	
Efficiency at Full Load	> 94% in Double-Conversion mode > 98% in Green mode	
Waveform	Sinewave	
Paralleling		
Parallel Redundancy	No	Yes (Optional box SRCPK0506)
Bypass Specifications		
Bypass Type	Internal Static Bypass (automatic & manual), Opt. External Bypass	
Bypass Input Voltage Range	170 V – 270V	
Max Bypass Current	40 A	
Input Protection	Circuit Breaker	
Battery Charger Specifications		
Supported Battery Types	SMF / Flooded	
Battery Bank Voltage	192 V	
Charger Power / Current	1500 W / 6.5 A max (selectable)	
Environmental Specifications		
Operating Temp	0 – 50°C (Output derated linearly to 75% of UPS capacity @ >40°C)	
Storage Temp	-15°C to 60°C	
Operating Elevation	1000m without derating	
Storage Elevation	15000m	
Humidity	0 to 95% RH, non-condensing	
Physical Specifications		
Dimensions without pack	13.4cm (W) x 43.3cm (H) x 70.6cm (D)	
Dimensions with packing	27.5cm (W) x 57cm (H) x 79cm (D)	
Weight without packing	18.8 kg	
Weight with packing	23.5 kg	

Accessories

Parallel Box

Now you can provide redundancy to your mission critical applications by using the new Parallel Box.

- 1+1 redundancy
- Rack/Tower configuration
- Single Phase
- UPS can be hotswapped for maintenance
- Compatible with SRCE6KUXI only



Accessory Cards & others

Choose from a host of Smart slot cards and other accessories to monitor environment and control devices connected to your UPS.

- AP9335TH : APC Temperature and Humidity Sensor
- APC9630 : APC UPS Network Management Card 2
- AP9631 : APC UPS NMC Card 2 with Environmental monitoring
- AP9810 : APC dry contact I/O accessory
- AP9613 : APC Dry contact I/O Smart Slot Card
- AP9624 : APC UPS Interface expander 2



Schneider Electric IT Business India Pvt. Ltd.
4th Floor, Electra, Wing 'A'
Prestige Tech Park
Exora Business parks
Marathahalli,
Sarjapur Outer Ring Road,
Bangalore - 560 103
Ph : +91 80 4333 3333
customer@apcc.com